

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 003_155
Product name: PULITORE UNIVERSALE 500ML PULISVELT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified Uses	Industrial	Professional	Consumer
glass cleaner	-	✓	✓

Uses Advised Against

Do not use for uses other than those indicated

1.3. Details of the supplier of the safety data sheet

Name: BERGEN S.r.l.
Full address: VIA ROMA, 90
District and Country: 37060 CASTEL D'AZZANO (VR)
Italia
Tel. +39 045512090
www.bergen.it

e-mail address of the competent person
responsible for the Safety Data Sheet

info@bergen.it

1.4. Emergency telephone number

For urgent inquiries refer to
BERGEN S.r.l.
+39 045512090
(08.30 - 17.30)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 3

H229

Pressurised container: may burst if heated.

Eye irritation, category 2

H319

Causes serious eye irritation.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Warning

Hazard statements:

H229 Pressurised container: may burst if heated.
H319 Causes serious eye irritation.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P280 Wear eye protection / face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

19,26% by mass of the contents are flammable.

Ingredients according to Regulation (EC) No. 648/2004

5% or over but less than 15% aliphatic hydrocarbons

perfumes, Coumarin

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
PROPAN-2-OL		

003_155 - PULITORE UNIVERSALE 500ML PULISVELT

CAS 67-63-0 13,5 ≤ x < 15 Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336

EC 200-661-7

INDEX 603-117-00-0

Reg. no. 01-2119457558-25

Hydrocarbons, C3-4

CAS 68476-40-4 5 ≤ x < 6 Flam. Gas 1A H220, Press. Gas H280

EC 270-681-9

INDEX 649-199-00-1

Reg. no. 01-2119486557-22

2-BUTOXYETHANOL

CAS 111-76-2 3,5 ≤ x < 4 Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315

EC 203-905-0

INDEX 603-014-00-0

Reg. no. 01-2119475108-36

SODIUM N-**LAUROYLSARCOSINATE**

CAS 137-16-6 0,15 ≤ x < 0,2 Acute Tox. 2 H330, Eye Dam. 1 H318, Skin Irrit. 2 H315

EC 205-281-5

INDEX -

Reg. no. 01-2119527780-39

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 5,00 %

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media**SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

Storage class TRGS 510 (Germany):
2B

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
DNK	Danmark	Bekendtgørelse om ændring af bekendtgørelse om grænseværdier for stoffer og materialer1- BEK nr 655 af 31/05/2018
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition,published 2018)
HRV	Hrvatska	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 91/18)
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
NLD	Nederland	Regeling van de Staatssecretaris van Sociale Zaken en Werkgelegenheid van 13 juli 2018, 2018-0000118517 tot wijziging van de Arbeidsomstandighedenregeling in verband met de implementatie van Richtlijn 2017/164 in Bijlage XIII
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
SVN	Slovenija	Uradni list Republike Slovenije 04.12.2018 - Uradnem listu RS št. 78 -PRAVILNIK o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2019

PROPAN-2-OL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	500	200	1000	400	
MAK	DEU	500	200	1000	400	
TLV	DNK	490	200			
VLA	ESP	500	200	1000	400	
VLEP	FRA			980	400	
WEL	GBR	999	400	1250	500	
GVI/KGVI	HRV	999	400	1250	500	
TGG	NLD	650				
NDS/NDSch	POL	900		1200		
MV	SVN	500	200			
TLV-ACGIH		492	200	983	400	
Predicted no-effect concentration - PNEC						

003_155 - PULITORE UNIVERSALE 500ML PULISVELT

Normal value in fresh water	140,9	mg/l
Normal value in marine water	140,9	mg/l
Normal value for fresh water sediment	552	mg/kg
Normal value for marine water sediment	552	mg/kg
Normal value for water, intermittent release	140,9	mg/l
Normal value of STP microorganisms	2251	mg/l
Normal value for the food chain (secondary poisoning)	160	mg/kg
Normal value for the terrestrial compartment	28	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				26 mg/kg bw/d				
Inhalation				89 mg/m3				500 mg/m3
Skin				319 mg/kg bw/d				888 mg/kg bw/d

Hydrocarbons, C3-4**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation				0.066 mg/m3				2.21 mg/m3
Skin								23.4 mg/kg bw/d

2-BUTOXYETHANOL**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	49	10	196	40	SKIN
MAK	DEU	49	10	98	20	SKIN
TLV	DNK	98	20			SKIN
VLA	ESP	98	20	245	50	SKIN
VLEP	FRA	49	10	246	50	SKIN
WEL	GBR	123	25	246	50	SKIN
GVI/KGVI	HRV	98	20	246	50	SKIN
VLEP	ITA	98	20	246	50	SKIN
TGG	NLD	100		246		SKIN
NDS/NDSch	POL	98		200		
VLE	PRT	98	20	246	50	SKIN
MV	SVN	98	20			SKIN
OEL	EU	98	20	246	50	SKIN
TLV-ACGIH		97	20			

Predicted no-effect concentration - PNEC

Normal value in fresh water	8,8	mg/l
Normal value in marine water	0,88	mg/l

Normal value for fresh water sediment	34,6	mg/kg
Normal value for marine water sediment	3,46	mg/kg
Normal value for water, intermittent release	9,1	mg/l
Normal value of STP microorganisms	463	mg/l
Normal value for the food chain (secondary poisoning)	20	mg/kg
Normal value for the terrestrial compartment	2,33	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		26,7 mg/kg bw/d		6,3 mg/kg bw/d				
Inhalation	147 mg/m3	426 mg/m3		59 mg/m3	246 mg/m3	1091 mg/m3		98 mg/m3
Skin		89 mg/kg bw/d		75 mg/kg bw/d				125 mg/kg bw/d

SODIUM N-LAUROYLSARCOSINATE

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,009	mg/l
Normal value in marine water	0,001	mg/l
Normal value for fresh water sediment	0,064	mg/kg
Normal value for marine water sediment	0,006	mg/kg
Normal value for water, intermittent release	0,089	mg/l
Normal value of STP microorganisms	3	mg/l
Normal value for the terrestrial compartment	0,008	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				10 mg/kg bw/d				
Inhalation				17,39 mg/m3				70,53 mg/m3
Skin				10 mg/kg bw/d				20 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type A filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	aerosol
Colour	colourless
Odour	characteristic
Odour threshold	Not available
pH	11,03
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	Not available
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	1,8 % (V/V)
Upper inflammability limit	9,5 % (V/V)
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	942
Solubility	soluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	lower propellant explosion limit: 1.8%
Oxidising properties	Not available

9.2. Other information

Information not available

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

2-BUTOXYETHANOL

Decomposes under the effect of heat.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

2-BUTOXYETHANOL

May react dangerously with: aluminium, oxidising agents. Forms peroxides with: air.

10.4. Conditions to avoid

Avoid overheating.

2-BUTOXYETHANOL

Avoid exposure to: sources of heat, naked flames.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

10.6. Hazardous decomposition products

2-BUTOXYETHANOL

May develop: hydrogen.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

> 20 mg/l

LD50 (Oral) of the mixture:

>2000 mg/kg

LD50 (Dermal) of the mixture:

>2000 mg/kg

2-BUTOXYETHANOL

LD50 (Oral) 615 mg/kg Rat

LD50 (Dermal) 405 mg/kg Rabbit

LC50 (Inhalation) 2,2 mg/l/4h Rat

SODIUM N-LAUROYLSARCOSINATE

LD50 (Oral) > 5000 mg/kg rat

LC50 (Inhalation) > 0,05 mg/l/4h rat

PROPAN-2-OL

LD50 (Oral) 5,84 mg/kg Rat

LD50 (Dermal) 16,4 ml/kg Rat

LC50 (Inhalation) 72,6 mg/l/4h Rat

Hydrocarbons, C3-4

LC50 (Inhalation) 505 mg//10 vale per 10 minuti e non 1h o 4h; rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

2-BUTOXYETHANOL

LC50 - for Fish	1250 mg//96h
EC50 - for Crustacea	> 1000 mg//48h
EC50 - for Algae / Aquatic Plants	911 mg//72h

Chronic NOEC for Crustacea	> 500 mg/l 48h
Chronic NOEC for Algae / Aquatic Plants	88 mg/l 72h
SODIUM N-LAUROYLSARCOSINATE	
LC50 - for Fish	32,1 mg/l/96h
EC50 - for Crustacea	8,91 mg/l/48h
EC50 - for Algae / Aquatic Plants	39 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	9,2 mg/l
PROPAN-2-OL	
LC50 - for Fish	9640 mg/l/96h
EC50 - for Crustacea	> 100 mg/l/48h
Hydrocarbons, C3-4	
LC50 - for Fish	24,11 mg/l/96h
EC50 - for Crustacea	14,22 mg/l/48h
EC50 - for Algae / Aquatic Plants	7,71 mg/l/96h vale per 96h e non 72h

12.2. Persistence and degradability

2-BUTOXYETHANOL	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable	
SODIUM N-LAUROYLSARCOSINATE	
Rapidly degradable	
PROPAN-2-OL	
Rapidly degradable	
Hydrocarbons, C3-4	
Rapidly degradable	

12.3. Bioaccumulative potential

2-BUTOXYETHANOL	
Partition coefficient: n-octanol/water	0,81
PROPAN-2-OL	
Partition coefficient: n-octanol/water	0,05

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number**

ADR / RID, IMDG, 1950
IATA:

14.2. UN proper shipping name

ADR / RID: AEROSOLS
IMDG: AEROSOLS
IATA: AEROSOLS, NON-FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID:	Class: 2	Label: 2.2
IMDG:	Class: 2	Label: 2.2
IATA:	Class: 2	Label: 2.2

**14.4. Packing group**

ADR / RID, IMDG, -
IATA:

14.5. Environmental hazards

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (E)
IMDG:	Special Provision: - EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 150 Kg	Packaging instructions: 203
	Pass.:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Special Instructions:	A98, A145, A167, A802	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point	40
---------------	----

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Regulation (EC) No. 648/2004

Ingredients according to Regulation (EC) No. 648/2004

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 1: Low hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A	Flammable gas, category 1A
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Press. Gas	Pressurised gas
Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 4	Acute toxicity, category 4
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
H220	Extremely flammable gas.
H229	Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may burst if heated.
H330	Fatal if inhaled.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

BERGEN S.r.l.	Revision nr. 1 Dated 03/03/2020 First compilation
003_155 - PULITORE UNIVERSALE 500ML PULISVELT	Printed on 03/03/2020 17/17

The data for evaluation of chemical-physical properties are reported in section 9.