

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 003_192
Product name: PULISCI VETRI & CRISTALLI PULISVELT
UFI: SVN5-Q1EU-J208-0GGM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified Uses	Industrial	Professional	Consumer
Glass cleaner	-	-	✓
multipurpose cleaner	-	-	✓

Uses Advised Against

Do not use for uses other than those indicated

1.3. Details of the supplier of the safety data sheet

Name: BERGEN S.r.l.
Full address: VIA ROMA, 90
District and Country: 37060 CASTEL D'AZZANO (VR)
Italia
Tel. +39 045512090

www.bergen.it

e-mail address of the competent person
responsible for the Safety Data Sheet

info@bergen.it

1.4. Emergency telephone number

For urgent inquiries refer to: BERGEN S.r.l.

+39 045512090

(08.30 - 17.30)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 2	H223 H229	Flammable aerosol. Pressurised container: may burst if heated.
Eye irritation, category 2	H319	Causes serious eye irritation.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Warning

Hazard statements:

H223	Flammable aerosol.
H229	Pressurised container: may burst if heated.
H319	Causes serious eye irritation.
EUH208	Contains: 2H-CHROMEN-2-ONE May produce an allergic reaction.

Precautionary statements:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P280	Wear eye protection / face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

Ingredients according to Regulation (EC) No. 648/2004

5% or over but less than 15% aliphatic hydrocarbons

perfumes, Coumarin

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\geq$ 0.1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
PROPAN-2-OL		
CAS 67-63-0	$13,5 \leq x < 15$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336
EC 200-661-7		
INDEX 603-117-00-0		
REACH Reg. 01-2119457558-25		
2-butoxyethanol		
CAS 111-76-2	$3,5 \leq x < 4$	Acute Tox. 3 H331, Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC 203-905-0		LD50 Oral: 1200 mg/l, STA Inhalation mists/powders: 0,501 mg/l
INDEX 603-014-00-0		
REACH Reg. 01-2119475108-36		
BUTANE		
CAS 106-97-8	$2,5 \leq x < 3$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C, U
EC 203-448-7		
INDEX 601-004-00-0		
PROPANE		
CAS 74-98-6	$1 \leq x < 1,5$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: U
EC 200-827-9		
INDEX 601-003-00-5		
REACH Reg. 01-2119486944-21		
SODIUM N-LAUROYLSARCOSINATE		
CAS 137-16-6	$0,15 \leq x < 0,2$	Acute Tox. 2 H330, Eye Dam. 1 H318, Skin Irrit. 2 H315
EC 205-281-5		LC50 Inhalation mists/powders: >0,05 mg/l/4h
INDEX -		
REACH Reg. 01-2119527780-39		
2H-CHROMEN-2-ONE		
CAS 91-64-5	$0 \leq x < 0,05$	Acute Tox. 4 H302, Skin Sens. 1A H317, Aquatic Chronic 3 H412
EC 202-086-7		STA Oral: 500 mg/kg
INDEX -		
REACH Reg. 01-2119943756-26		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 5,00 %

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in

compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

Storage class TRGS 510 (Germany):
2B

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία``»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006

SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov Pravilník o varovaní delavcov pred tveganí zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19) EH40/2005 Workplace exposure limits (Fourth Edition 2020) Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC. ACGIH 2021
SVN	Slovenija	
GBR	United Kingdom	
EU	OEL EU	
	TLV-ACGIH	

PROPAN-2-OL								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	980		1225				
TLV	CZE	500		1000		SKIN		
AGW	DEU	500	200	1000	400			
MAK	DEU	500	200	1000	400			
TLV	DNK	490	200					
VLA	ESP	500	200	1000	400			
VLEP	FRA			980	400			
TLV	GRC	980	400	1225	500			
AK	HUN	500		2000				
GVI/KGVI	HRV	999	400	1250	500			
TGG	NLD	650						
NDS/NDSch	POL	900		1200				
NPEL	SVK	500	200	1000				
MV	SVN	500	200					
WEL	GBR	999	400	1250	500			
TLV-ACGIH		492	200	983	400			
Predicted no-effect concentration - PNEC								
Normal value in fresh water				140,9		mg/l		
Normal value in marine water				140,9		mg/l		
Normal value for fresh water sediment				552		mg/kg		
Normal value for marine water sediment				552		mg/kg		
Normal value for water, intermittent release				140,9		mg/l		
Normal value of STP microorganisms				2251		mg/l		
Normal value for the food chain (secondary poisoning)				160		mg/kg		
Normal value for the terrestrial compartment				28		mg/kg		
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				26 mg/kg bw/d				
Inhalation				89 mg/m3				500 mg/m3
Skin				319 mg/kg bw/d				888 mg/kg bw/d

2-butoxyethanol								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	98		246		SKIN		
TLV	CZE	100		200		SKIN		
AGW	DEU	49	10	196	40	SKIN		
MAK	DEU	49	10	98	20	SKIN		
TLV	DNK	98	20			SKIN		
VLA	ESP	98	20	245	50	SKIN		
VLEP	FRA	49	10	246	50	SKIN		
TLV	GRC	120	25					
AK	HUN	98		246				
GVI/KGVI	HRV	98	20	246	50	SKIN		
VLEP	ITA	98	20	246	50	SKIN		
TGG	NLD	100		246		SKIN		
VLE	PRT	98	20	246	50	SKIN		
NDS/NDSch	POL	98		200				
NPEL	SVK	98	20	246		SKIN		
MV	SVN	98	20			SKIN		
WEL	GBR	123	25	246	50	SKIN		
OEL	EU	98	20	246	50	SKIN		
TLV-ACGIH		97	20					
Predicted no-effect concentration - PNEC								
Normal value in fresh water				8,8	mg/l			
Normal value in marine water				0,88	mg/l			
Normal value for fresh water sediment				34,6	mg/kg			
Normal value for marine water sediment				3,46	mg/kg			
Normal value for water, intermittent release				26,4	mg/l			
Normal value of STP microorganisms				463	mg/l			
Normal value for the food chain (secondary poisoning)				20	mg/kg food			
Normal value for the terrestrial compartment				2,33	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		26,7 mg/kg bw/d		6,3 mg/kg bw/d				
Inhalation	147 mg/m3	426 mg/m3		59 mg/m3	246 mg/m3	1091 mg/m3		98 mg/m3
Skin		89 mg/kg bw/d		75 mg/kg bw/d		89 mg/kg bw/d		125 mg/kg bw/d
BUTANE								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		

		mg/m3	ppm	mg/m3	ppm
TLV	BGR	1900			
AGW	DEU	2400	1000	9600	4000
MAK	DEU	2400	1000	9600	4000
TLV	DNK	1200	500		
VLA	ESP		1000		Gases
VLEP	FRA	1900	800		
TLV	GRC	2350	1000		
AK	HUN	2350		9400	
GVI/KGVI	HRV	1450	600	1810	750
TGG	NLD	1430			
NDS/NDSCh	POL	1900		3000	
MV	SVN	2400	1000	9600	4000
WEL	GBR	1450	600	1810	750
WEL	GBR		4		RESP
TLV-ACGIH					1000

PROPANE					
Threshold Limit Value					
Type	Country	TWA/8h		STEL/15min	Remarks / Observations
		mg/m3	ppm	mg/m3	ppm
TLV	BGR	1800			
AGW	DEU	1800	1000	7200	4000
MAK	DEU	1800	1000	7200	4000
TLV	DNK	1800	1000		
VLA	ESP		1000		
TLV	GRC	1800	1000		
NDS/NDSCh	POL	1800			
TLV	ROU	1400	778	1800	1000
MV	SVN	1800	1000	7200	4000

SODIUM N-LAUROYLSARCOSINATE								
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,009		mg/l		
Normal value in marine water				0,001		mg/l		
Normal value for fresh water sediment				0,064		mg/kg		
Normal value for marine water sediment				0,006		mg/kg		
Normal value for water, intermittent release				0,089		mg/l		
Normal value of STP microorganisms				3		mg/l		
Normal value for the terrestrial compartment				0,008		mg/kg		
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic

003_192 - PULISCI VETRI & CRISTALLI PULISVELT

Oral	10 mg/kg bw/d	
Inhalation	17,39 mg/m3	70,53 mg/m3
Skin	10 mg/kg bw/d	20 mg/kg bw/d

2H-CHROMEN-2-ONE

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,019	mg/l
Normal value in marine water	0,0019	mg/l
Normal value for fresh water sediment	0,15	mg/kg
Normal value for marine water sediment	0,015	mg/kg
Normal value for water, intermittent release	0,0142	mg/l
Normal value of STP microorganisms	6,4	mg/l
Normal value for the food chain (secondary poisoning)	30,7	mg/kg
Normal value for the terrestrial compartment	0,018	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,39 mg/kg bw/d				
Inhalation				1,69 mg/m3				6,78 mg/m3
Skin				0,39 mg/kg bw/d				0,79 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter

combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	aerosol	Method: not specified
Colour	colourless	
Odour	characteristic	Method: not specified
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	1,8 % (v/v)	Method: Non specificato
Upper explosive limit	9,5 % (v/v)	Method: Non specificato
Flash point	not available	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	11,2	Method: not specified Remark: liquid
Kinematic viscosity	not available	
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	94 g/cm ³	Method: not specified
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids { 0}	not available	Method: not specified
VOC (Directive 2010/75/EU)	22,15 % - 20.817,97 g/litre	
Explosive properties	lower propellant explosion limit: 1.8%	Method: not specified

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-butoxyethanol

Decomposes under the effect of heat.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

2-butoxyethanol

May react dangerously with: aluminium, oxidising agents. Forms peroxides with: air.

10.4. Conditions to avoid

Avoid overheating.

2-butoxyethanol

Avoid exposure to: sources of heat, naked flames.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

10.6. Hazardous decomposition products

2-butoxyethanol

May develop: hydrogen.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

003_192 - PULISCI VETRI & CRISTALLI PULISVELT

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	> 5 mg/l
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	Not classified (no significant component)

PROPAN-2-OL

LD50 (Dermal):	16,4 ml/kg Rat
LD50 (Oral):	5,84 mg/kg Rat
LC50 (Inhalation vapours):	72,6 mg/l/4h Rat

2-butoxyethanol

LD50 (Dermal):	435 mg/kg bw Male Rabbit
LD50 (Oral):	1200 mg/kg bw Guinea pig
LC50 (Inhalation vapours):	3 mg/l Rat
STA (Inhalation mists/powders):	0,501 mg/l (figure used for calculation of the acute toxicity estimate of the mixture)

BUTANE

LC50 (Inhalation gas):	1443 mg/l
------------------------	-----------

SODIUM N-LAUROYLSARCOSINATE

LD50 (Oral):	> 5000 mg/kg rat
LC50 (Inhalation mists/powders):	> 0,05 mg/l/4h rat

2H-CHROMEN-2-ONE

LD50 (Dermal):	293 mg/kg bw rat
LD50 (Oral):	290 mg/kg bw rat

003_192 - PULISCI VETRI & CRISTALLI PULISVELT

LC50 (Inhalation mists/powders):

293 mg/kg rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

2H-CHROMEN-2-ONE

Respiratory sensitization

Information not available

Skin sensitization

Information not available

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Adverse effects on sexual function and fertility

Information not available

Adverse effects on development of the offspring

Information not available

Effects on or via lactation

Information not available

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available

Route of exposure

Information not available

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available

Route of exposure

Information not available

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

BUTANE

LC50 - for Fish	24,11 mg/l/96h
EC50 - for Crustacea	7,02 mg/l/48h
EC50 - for Algae / Aquatic Plants	7,71 mg/l/72h

2-butoxyethanol

LC50 - for Fish	1250 mg/l/96h Menidia beryllina
EC50 - for Crustacea	> 370 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	623 mg/l/72h Pseudokirchneriella subcapitata
Chronic NOEC for Crustacea	> 500 mg/l/48 h Daphnia magna
Chronic NOEC for Algae / Aquatic Plants	62,5 mg/l/72 h Pseudokirchneriella subcapitata

SODIUM N-LAUROYLSARCOSINATE

LC50 - for Fish	32,1 mg/l/96h
EC50 - for Crustacea	8,91 mg/l/48h
EC50 - for Algae / Aquatic Plants	39 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	9,2 mg/l

PROPAN-2-OL

LC50 - for Fish	9640 mg/l/96h
EC50 - for Crustacea	> 100 mg/l/48h

PROPANE

LC50 - for Fish	24,11 mg/l/96h
EC50 - for Crustacea	7,02 mg/l/96h

EC50 - for Algae / Aquatic Plants 7,71 mg/l/72h

2H-CHROMEN-2-ONE

LC50 - for Fish 1,324 mg/l/96h

EC50 - for Crustacea 8,012 mg/l/48h

EC50 - for Algae / Aquatic Plants 1,452 mg/l/72h

Chronic NOEC for Fish 0,119 mg/l

Chronic NOEC for Crustacea 0,448 mg/l

Chronic NOEC for Algae / Aquatic Plants 0,408 mg/l

12.2. Persistence and degradability

BUTANE

Solubility in water 0,1 - 100 mg/l

Rapidly degradable

2-butoxyethanol

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

SODIUM N-LAUROYLSARCOSINATE

Rapidly degradable

PROPAN-2-OL

Rapidly degradable

PROPANE

Solubility in water 0,1 - 100 mg/l

Rapidly degradable

2H-CHROMEN-2-ONE

Rapidly degradable

12.3. Bioaccumulative potential

BUTANE

Partition coefficient: n-octanol/water 1,09

2-butoxyethanol

Partition coefficient: n-octanol/water 0,81

PROPAN-2-OL

Partition coefficient: n-octanol/water 0,05

PROPANE

Partition coefficient: n-octanol/water 1,09

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1950

14.2. UN proper shipping name

ADR / RID: AEROSOLS

IMDG: AEROSOLS

IATA: AEROSOLS, NON-FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.2

IMDG: Class: 2 Label: 2.2

IATA: Class: 2 Label: 2.2



14.4. Packing group

ADR / RID, IMDG, IATA: -

14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: --

Limited
Quantities: 1
LTunnel
restriction
code: (E)IMDG: Special provision: -
EMS: F-D, S-ULimited
Quantities: 1
L

IATA: Cargo:

Maximum
quantity: 150
KgPackaging
instructions:
203

Pass.:

Maximum
quantity: 75
KgPackaging
instructions:
203

Special provision:

A98, A145,
A167, A802**14.7. Maritime transport in bulk according to IMO instruments**

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EU: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006Product

Point 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Regulation (EC) No. 648/2004

Ingredients according to Regulation (EC) No. 648/2004

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 1: Low hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A	Flammable gas, category 1A
Aerosol 2	Aerosol, category 2
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Press. Gas (Liq.)	Liquefied gas
Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 4	Acute toxicity, category 4

003_192 - PULISCI VETRI & CRISTALLI PULISVELT

Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1A	Skin sensitization, category 1A
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H220	Extremely flammable gas.
H223	Flammable aerosol.
H229	Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may burst if heated.
H330	Fatal if inhaled.
H302	Harmful if swallowed.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament

3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (EU) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 06 / 08 / 09 / 11 / 12 / 15 / 16.