

003_338 - DISINCROSTANTE WC MOUSSE PULISVELT

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 003_338
Product name: DISINCROSTANTE WC MOUSSE PULISVELT
UFI: ANVC-D6WD-W00E-ND2T

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified Uses	Industrial	Professional	Consumer
Descaler	-	-	✓

Uses Advised Against

Do not use for uses other than those indicated

1.3. Details of the supplier of the safety data sheet

Name: BERGEN S.r.l.
Full address: VIA ROMA, 90
District and Country: 37060 CASTEL D'AZZANO (VR)
Italia
Tel. +39 045512090
www.bergen.it

e-mail address of the competent person

responsible for the Safety Data Sheet: info@bergen.it**1.4. Emergency telephone number**

For urgent inquiries refer to: BERGEN S.r.l.
+39 045512090
(08.30 - 17.30)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222 H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
Skin corrosion, category 1A	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.

003_338 - DISINCROSTANTE WC MOUSSE PULISVELT**2.2. Label elements**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H314 Causes severe skin burns and eye damage.

Precautionary
statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

P211 Do not spray on an open flame or other ignition source.

P260 Do not breathe dust / fume / gas / mist / vapours / spray.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P501 Dispose of contents / container in accordance with current regulations.

Contains: SODIUM HYDROXIDE

Ingredients according to Regulation (EC) No. 648/2004

Less than 5%	Non-ionic surfactants
5% or over but less than 15%	Aliphatic hydrocarbons

Limonene, Perfumes

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
CITRIC ACID MONOHYDRATE		
INDEX -	4,5 ≤ x < 5	Eye Irrit. 2 H319, STOT SE 3 H335
EC 201-069-1		
CAS 5949-29-1		
REACH Reg. 01-2119457026-42		
BUTANE		
INDEX 601-004-00-0	3 ≤ x < 3,5	Flam. Gas 1A H220, Press. Gas H280, Classification note according to Annex VI to the CLP Regulation: C, U
EC 203-448-7		
CAS 106-97-8		
REACH Reg. 01-2119474691-32		
SODIUM HYDROXIDE		
INDEX 011-002-00-6	2,5 ≤ x < 3	Met. Corr. 1 H290, Skin Corr. 1A H314, Eye Dam. 1 H318
EC 215-185-5		Skin Corr. 1B H314: ≥ 2%, Skin Irrit. 2 H315: ≥ 0,5%, Eye Dam. 1 H318: ≥ 2%, Eye Irrit. 2 H319: ≥ 0,5%
CAS 1310-73-2		
REACH Reg. 01-2119457892-27		
ALCOHOLS C12-14, ETHOXYLATED (>2-5EO)		
INDEX -	2,5 ≤ x < 3	Acute Tox. 4 H302, Eye Dam. 1 H318, Aquatic Chronic 3 H412
EC 932-106-6		Eye Dam. 1 H318: ≥ 10%, Eye Irrit. 2 H319: ≥ 3%
CAS 68439-50-9		STA Oral: 500 mg/kg
PROPANE		
INDEX 601-003-00-5	1,5 ≤ x < 2	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: U
EC 200-827-9		
CAS 74-98-6		
REACH Reg. 01-2119486944-21		
isobutane		
INDEX 601-004-00-0	1 ≤ x < 1,5	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C, U

003_338 - DISINCROSTANTE WC MOUSSE PULISVELT

EC 200-857-2

CAS 75-28-5

REACH Reg. 01-2119485395-27

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 6,26 %

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

Storage class TRGS 510 (Germany):

2B

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte.

DNK	Danmark	MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
FRA	France	Límites de exposición profesional para agentes químicos en España 2021
FIN	Suomi	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 2020:25 Π.Δ. 26/2020 (ΦΕΚ 50/Α΄ 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία``»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom TLV-ACGIH	EH40/2005 Workplace exposure limits (Fourth Edition 2020) ACGIH 2022

CITRIC ACID MONOHYDRATE		
Predicted no-effect concentration - PNEC		
Normal value in fresh water	0,44	mg/l
Normal value in marine water	0,044	mg/l
Normal value for fresh water sediment	34,6	mg/kg
Normal value for marine water sediment	3,46	mg/kg
Normal value of STP microorganisms	1000	mg/l
Normal value for the terrestrial compartment	33,1	mg/kg

BUTANE						
Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	1900				
AGW	DEU	2400	1000	9600	4000	
MAK	DEU	2400	1000	9600	4000	
TLV	DNK	1200	500			
VLA	ESP		1000			Gases
VLEP	FRA	1900	800			
HTP	FIN	1900	800	2400	1000	
TLV	GRC	2350	1000			
AK	HUN	2350		9400		
GVI/KGVI	HRV	1450	600	1810	750	
TLV	NOR	600	250			

BERGEN S.r.l.						Revision nr. 1			
003_338 - DISINCROSTANTE WC MOUSSE PULISVELT						Dated 05/07/2023			
						First compilation			
						Printed on 10/07/2023			
						7/18			
TGG	NLD	1430							
NDS/NDSch	POL	1900		3000					
MV	SVN	2400	1000	9600	4000				
WEL	GBR	1450	600	1810	750				
WEL	GBR		4			RESP			
TLV-ACGIH					1000				
SODIUM HYDROXIDE									
Threshold Limit Value									
Type	Country	TWA/8h		STEL/15min		Remarks /			
						Observations			
		mg/m3	ppm	mg/m3	ppm				
TLV	BGR	2							
TLV	CZE	1		2					
TLV	DNK	2							
VLA	ESP	2							
VLEP	FRA	2							
HTP	FIN			2 (C)					
TLV	GRC	2		2					
AK	HUN	2		2					
GVI/KGVI	HRV			2					
NDS/NDSch	POL	0,5		1					
NPEL	SVK	2							
WEL	GBR			2					
TLV-ACGIH				2 (C)					
Health - Derived no-effect level - DNEL / DMEL									
		Effects on consumers			Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic	
Inhalation			1 mg/m3				1 mg/m3		
PROPANE									
Threshold Limit Value									
Type	Country	TWA/8h		STEL/15min		Remarks /			
						Observations			
		mg/m3	ppm	mg/m3	ppm				
TLV	BGR	1800							
AGW	DEU	1800	1000	7200	4000				
MAK	DEU	1800	1000	7200	4000				
TLV	DNK	1800	1000						
VLA	ESP		1000						
HTP	FIN	1500	800	2000	1100				
TLV	GRC	1800	1000						
TLV	NOR	900	500						
NDS/NDSch	POL	1800							
TLV	ROU	1400	778	1800	1000				
MV	SVN	1800	1000	7200	4000				

isobutane					
Threshold Limit Value					
Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	2400	1000	9600	4000
MAK	DEU	2400	1000	9600	4000
HTP	FIN	1900	800	2400	1000

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties		
Properties	Value	Information
Appearance	aerosol	
Colour	white	
Odour	characteristic	Method:BG SM 18
Melting point / freezing point	-159 °C	Method:not specified

BERGEN S.r.l.		Revision nr. 1 Dated 05/07/2023 First compilation Printed on 10/07/2023 9/18
003_338 - DISINCROSTANTE WC MOUSSE PULISVELT		
Initial boiling point	-16 °C	Remark:propellant Method:not specified Remark:propellant
Flammability	Flame height ≥4cm and flame duration ≥7s	Method:BGPF11
Lower explosive limit	1,4	Method:Not specified Remark:propellant
Upper explosive limit	11,2	Method:Not specified Remark:propellant
Flash point	not available	Reason for missing data:substance/mixture is a gas
Auto-ignition temperature	470 °C	Method:not specified Remark:propellant
Decomposition temperature	not available	Reason for missing data:It only applies to authoritative substances and mixtures, organic peroxides and other substances and mixtures that they can decompose
pH	12,23	Method:internal method Remark:value referred to the liquid phase Temperature: 20 °C
Kinematic viscosity	not available	Reason for missing data:not determined
Solubility	not available	Reason for missing data:substance/mixture is a gas
Partition coefficient: n-octanol/water	2,79	Method:not specified Remark:propellant
Vapour pressure	da 2,5 a 3,2 Bar	Method:not specified Remark:propellant Temperature: 20 °C
Density and/or relative density	1,049 g/l	Method:BG SM 17 Remark:liquid phase Temperature: 20 °C
Relative vapour density	>1	Method:not specified Remark:propellant
Particle characteristics		
Median equivalent diameter		
Remark:	It only applies to solids	
Size distribution		
Remark:	It only applies to solids	
Dustiness		
Remark:	It only applies to solids	
Specific surface area		
Remark:	It only applies to solids	
Shape		
Remark:	It only applies to solids	
9.2. Other information		
9.2.1. Information with regard to physical hazard classes		
Information not available		
9.2.2. Other safety characteristics		

Explosive properties

Lower propelled explosion
limit: 1.4 %

Method: not specified

Oxidising properties

No oxidizing property

Method: internal

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

Avoid overheating.

SODIUM HYDROXIDE

Avoid exposure to: air, moisture, sources of heat.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

SODIUM HYDROXIDE

Incompatible with: strong acids, ammonia, zinc, lead, aluminium, water, flammable liquids.

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

003_338 - DISINCROSTANTE WC MOUSSE PULISVELT

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	Not classified (no significant component)

CITRIC ACID MONOHYDRATE

LD50 (Dermal):	> 2000 mg/kg Rat
LD50 (Oral):	5400 mg/kg Mouse

BUTANE

LC50 (Inhalation gas):	1443 mg/l
------------------------	-----------

SODIUM HYDROXIDE

LD50 (Oral):	325 mg/kg bw
--------------	--------------

ALCOHOLS C12-14, ETHOXYLATED (>2-5EO)

STA (Oral):	500 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
-------------	--

isobutane

LC50 (Inhalation gas):	1443 mg/l
------------------------	-----------

SKIN CORROSION / IRRITATION

BERGEN S.r.l.	Revision nr. 1
	Dated 05/07/2023
003_338 - DISINCROSTANTE WC MOUSSE PULISVELT	First compilation
	Printed on 10/07/2023
	12/18

Corrosive for the skin

Classification according to the experimental Ph value

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

003_338 - DISINCROSTANTE WC MOUSSE PULISVELT

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity**BUTANE**

LC50 - for Fish	24,11 mg/l/96h
EC50 - for Crustacea	7,02 mg/l/48h
EC50 - for Algae / Aquatic Plants	7,71 mg/l/72h

SODIUM HYDROXIDE

LC50 - for Fish	< 180 mg/l/96h <i>Gambusia affinis</i>
EC50 - for Crustacea	40,4 mg/l/48h <i>Ceriodaphnia</i> sp.

CITRIC ACID MONOHYDRATE

LC50 - for Fish	> 100 mg/l/96h
EC50 - for Crustacea	> 50 mg/l/48h
Chronic NOEC for Algae / Aquatic Plants	425 mg/l

PROPANE

LC50 - for Fish	24,11 mg/l/96h
EC50 - for Crustacea	7,02 mg/l/96h
EC50 - for Algae / Aquatic Plants	7,71 mg/l/72h

isobutane

LC50 - for Fish	24,11 mg/l/96h
EC50 - for Algae / Aquatic Plants	7,71 mg/l/72h

12.2. Persistence and degradability**BUTANE**

Solubility in water	0,1 - 100 mg/l
---------------------	----------------

Rapidly degradable

SODIUM HYDROXIDE

Degradability: information not available

CITRIC ACID MONOHYDRATE

Rapidly degradable

BERGEN S.r.l.	Revision nr. 1 Dated 05/07/2023 First compilation
003_338 - DISINCROSTANTE WC MOUSSE PULISVELT	Printed on 10/07/2023 14/18

PROPANE
Solubility in water 0,1 - 100 mg/l
Rapidly degradable

12.3. Bioaccumulative potential

BUTANE
Partition coefficient: n-octanol/water 1,09

CITRIC ACID MONOHYDRATE
BCF 3,2

PROPANE
Partition coefficient: n-octanol/water 1,09

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
Waste transportation may be subject to ADR restrictions.
CONTAMINATED PACKAGING
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1950

003_338 - DISINCROSTANTE WC MOUSSE PULISVELT

14.2. UN proper shipping name

ADR / RID: AEROSOLS
 IMDG: AEROSOLS
 IATA: AEROSOLS, FLAMMABLE, CONTAINING SUBSTANCE IN CLASS 8

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1 (8)

IMDG: Class: 2 Label: 2.1 (8)

IATA: Class: 2 Label: 2.1 (8)



14.4. Packing group

ADR / RID, IMDG, IATA: -

14.5. Environmental hazards

ADR / RID: NO
 IMDG: NO
 IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
	Special provision: 190, 327, 344, 625		
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 150 Kg	Packaging instructions: 203
	Passengers:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Special provision:	A145, A167, A802	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

003_338 - DISINCROSTANTE WC MOUSSE PULISVELT

Seveso Category - Directive 2012/18/EU: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Regulation (EC) No. 648/2004

Ingredients according to Regulation (EC) No. 648/2004

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 1: Low hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A	Flammable gas, category 1A
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Press. Gas	Pressurised gas
Press. Gas (Liq.)	Liquefied gas
Met. Corr. 1	Substance or mixture corrosive to metals, category 1
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1A	Skin corrosion, category 1A
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H280	Contains gas under pressure; may explode if heated.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train

003_338 - DISINCROSTANTE WC MOUSSE PULISVELT

- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2019/521 (XII Atp. CLP)
 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
 17. Regulation (EU) 2019/1148
 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.