

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 003_111
Product name: DEO MATIC RICARICA TALCO AIR FLOR
UFI : 49Y9-4E1N-VN0U-02VQ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified Uses	Industrial	Professional	Consumer
Room deodorant	-	-	✓

Uses Advised Against

Do not use for uses other than those indicated

1.3. Details of the supplier of the safety data sheet

Name: BERGEN S.r.l.
Full address: VIA ROMA, 90
District and Country: 37060 CASTEL D'AZZANO (VR)
Italia
Tel. +39 045512090

www.bergen.it

e-mail address of the competent person

responsible for the Safety Data Sheet: info@bergen.it

1.4. Emergency telephone number

For urgent inquiries refer to: BERGEN S.r.l.

+39 045512090

(08.30 - 17.30)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222 H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
P501	Dispose of contents / container in accordance with current regulations.
P211	Do not spray on an open flame or other ignition source.
P280	Wear protective gloves / eye protection / face protection.
P271	Use only outdoors or in a well-ventilated area.
P102	Keep out of reach of children.
P101	If medical advice is needed, have product container or label at hand.

Contains:	(S)-p-mentha-1,8-diene LINALYL ACETATE propan-2-ol ALPHA-ISOMETHYL IONONE geraniol 2H-CHROMEN-2-ONE linalool PIPERONAL
------------------	---

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\geq$ 0.1%.

SECTION 3. Composition/information on ingredients

003_111 - DEO MATIC RICARICA TALCO AIR FLOR

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
BUTANE		
CAS 106-97-8	$45 \leq x < 47,5$	Flam. Gas 1A H220, Press. Gas H280, Classification note according to Annex VI to the CLP Regulation: C, U
EC 203-448-7		
INDEX 601-004-00-0		
REACH Reg. 01-2119474691-32		
PROPANE		
CAS 74-98-6	$22,5 \leq x < 24$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: U
EC 200-827-9		
INDEX 601-003-00-5		
REACH Reg. 01-2119486944-21		
isobutane		
CAS 75-28-5	$16,5 \leq x < 18$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C, U
EC 200-857-2		
INDEX 601-004-00-0		
REACH Reg. 01-2119485395-27		
propan-2-ol		
CAS 67-63-0	$10 \leq x < 11,5$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336
EC 200-661-7		
INDEX 603-117-00-0		
REACH Reg. 01-2119457558-25		
LINALYL ACETATE		
CAS 115-95-7	$0,2 \leq x < 0,25$	Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1B H317
EC 204-116-4		
INDEX -		
REACH Reg. 01-2119454789-19		
(S)-p-mentha-1,8-diene		
CAS 5989-54-8	$0,1 \leq x < 0,15$	Flam. Liq. 3 H226, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
EC 227-815-6		
INDEX 601-029-00-7		
REACH Reg. 01-2119958629-18		
musk ketone		
CAS 81-14-1	$0,1 \leq x < 0,15$	Carc. 2 H351, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
EC 201-328-9		
INDEX 609-069-00-7		
PIPERONAL		

003_111 - DEO MATIC RICARICA TALCO AIR FLOR

CAS 120-57-0 $0,1 \leq x < 0,15$ Skin Sens. 1B H317

EC 204-409-7

INDEX -

REACH Reg. 01-2119983608-21

linalool

CAS 78-70-6 $0,05 \leq x < 0,1$ Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1B H317

EC 201-134-4

INDEX 603-235-00-2

REACH Reg. 01-2119474016-42

2H-CHROMEN-2-ONE

CAS 91-64-5 $0,05 \leq x < 0,1$ Acute Tox. 4 H302, Skin Sens. 1 H317, Aquatic Chronic 3 H412

EC 202-086-7

STA Oral: 500 mg/kg

INDEX -

REACH Reg. 01-2119943756-26

geraniol

CAS 106-24-1 $0,05 \leq x < 0,1$ Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1 H317

EC 203-377-1

INDEX 603-241-00-5

REACH Reg. 01-2119552430-49

ALPHA-ISOMETHYL IONONE

CAS 127-51-5 $0 \leq x < 0,05$ Skin Sens. 1 H317, Aquatic Chronic 2 H411

EC 204-846-3

INDEX -

REACH Reg. 01-2120138569-45

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 87,96 %

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

Storage class TRGS 510 (Germany):
2B

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία``»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom TLV-ACGIH	EH40/2005 Workplace exposure limits (Fourth Edition 2020) ACGIH 2021

BUTANE					
Threshold Limit Value					
Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV	BGR	1900			
AGW	DEU	2400	1000	9600	4000
MAK	DEU	2400	1000	9600	4000
TLV	DNK	1200	500		

VLA	ESP	1000	Gases		
VLEP	FRA	1900	800		
TLV	GRC	2350	1000		
AK	HUN	2350	9400		
GVI/KGVI	HRV	1450	600	1810	750
TGG	NLD	1430			
NDS/NDSch	POL	1900	3000		
MV	SVN	2400	1000	9600	4000
WEL	GBR	1450	600	1810	750
WEL	GBR	4		RESP	
TLV-ACGIH				1000	

PROPANE					
Threshold Limit Value					
Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV	BGR	1800			
AGW	DEU	1800	1000	7200	4000
MAK	DEU	1800	1000	7200	4000
TLV	DNK	1800		1000	
VLA	ESP	1000			
TLV	GRC	1800	1000		
NDS/NDSch	POL	1800			
TLV	ROU	1400	778	1800	1000
MV	SVN	1800	1000	7200	4000

isobutane					
Threshold Limit Value					
Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	2400	1000	9600	4000
MAK	DEU	2400	1000	9600	4000

propan-2-ol					
Threshold Limit Value					
Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV	BGR	980		1225	
TLV	CZE	500	200	1000	400
AGW	DEU	500	200	1000	400
MAK	DEU	500	200	1000	400
TLV	DNK	490	200		
VLA	ESP	500	200	1000	400
VLEP	FRA			980	400

BERGEN S.r.l.						Revision nr. 7		
003_111 - DEO MATIC RICARICA TALCO AIR FLOR						Dated 26/04/2023		
						Printed on 26/04/2023		
						8/25		
						Replaced revision:6 (Dated: 26/04/2023)		
TLV	GRC	980	400	1225	500			
AK	HUN	500		1000		SKIN		
GVI/KGVI	HRV	999	400	1250	500			
TGG	NLD	650						
NDS/NDSch	POL	900		1200		SKIN		
TLV	ROU	200	81	500	203			
NPEL	SVK	500	200	1000	400			
MV	SVN	500	200	2000	800			
WEL	GBR	999	400	1250	500			
TLV-ACGIH		492	200	983	400			
Predicted no-effect concentration - PNEC								
Normal value in fresh water				1409	mg/l			
Normal value in marine water				1409	mg/l			
Normal value for fresh water sediment				552	mg/kg			
Normal value for marine water sediment				552	mg/kg			
Normal value for water, intermittent release				1409	mg/l			
Normal value of STP microorganisms				2251	mg/l			
Normal value for the food chain (secondary poisoning)				160	mg/kg			
Normal value for the terrestrial compartment				28	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		51 mg/kg bw/d		26 mg/kg bw/d				
Inhalation		178 mg/m3		89 mg/m3		1000 mg/m3		500 mg/m3
Skin				319 mg/kg bw/d				888 mg/kg bw/d
LINALYL ACETATE								
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,011	mg/l			
Normal value in marine water				0,001	mg/l			
Normal value for fresh water sediment				0,609	mg/kg			
Normal value for marine water sediment				0,061	mg/kg			
Normal value for water, intermittent release				0,11	mg/l			
Normal value of STP microorganisms				10	mg/l			
Normal value for the terrestrial compartment				0,115	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,2 mg/kg bw/d				
Inhalation				0,68 mg/m3				2,75 mg/m3
Skin	8 mg/cm2		8 mg/cm2	1,25 mg/kg bw/d			8 mg/cm2	2,5 mg/kg bw/d
(S)-p-mentha-1,8-diene								

003_111 - DEO MATIC RICARICA TALCO AIR FLOR

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,0054	mg/l
Normal value in marine water	0,00054	mg/l
Normal value for fresh water sediment	1,322	mg/kg/d
Normal value for marine water sediment	0,132	mg/kg
Normal value for water, intermittent release	0,0036	mg/l
Normal value of STP microorganisms	0,2	mg/l
Normal value for the food chain (secondary poisoning)	133	mg/kg
Normal value for the terrestrial compartment	0,262	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				4,76 mg/kg bw/d				
Inhalation				8,33 mg/m3				33,3 mg/m3
Skin	0,111 mg/cm2				0,022 mg/cm2			

PIPERONAL

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,0025	mg/l
Normal value in marine water	0,00025	mg/l
Normal value for fresh water sediment	0,0119	mg/kg
Normal value for marine water sediment	0,0012	mg/kg
Normal value for water, intermittent release	0,025	mg/l
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	0,00084	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				1,25 mg/kg bw/d				
Inhalation				4,3 mg/m3				17,6 mg/m3
Skin				1,25 mg/kg bw/d				2,5 mg/kg bw/d

musk ketone

Predicted no-effect concentration - PNEC

Normal value in fresh water	244	µg/L
Normal value in marine water	244	ng/L
Normal value for fresh water sediment	61,8	µg/kg/d
Normal value for marine water sediment	6,18	µg/kg/d
Normal value for water, intermittent release	244	µg/L
Normal value of STP microorganisms	10	mg/l
Normal value for the food chain (secondary poisoning)	VND	
Normal value for the terrestrial compartment	12,2	µg/kg/d
Normal value for the atmosphere	NPI	

003_111 - DEO MATIC RICARICA TALCO AIR FLOR

Normal value in fresh water	0,011	mg/l
Normal value in marine water	0,001	mg/l
Normal value for fresh water sediment	0,115	mg/kg
Normal value for marine water sediment	0,011	mg/kg
Normal value for water, intermittent release	0,108	mg/l
Normal value of STP microorganisms	0,7	mg/l
Normal value for the terrestrial compartment	0,017	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				13,75 mg/kg bw/d				
Inhalation			11,8	47,8 mg/m3				161,6 mg/m3
Skin			11,8 mg/cm2	7,5 mg/kg bw/d			11,8 mg/cm2	12,5 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

003_111 - DEO MATIC RICARICA TALCO AIR FLOR

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	aerosol	
Colour	transparent	
Odour	characteristic	Method:internal
Melting point / freezing point	-159 °C	Method:not specified Remark:propellant
Initial boiling point	-16 °C	Method:not specified Remark:propellant
Flammability	In testing the ignition distance, the ignition takes place at a distance > = 15 cm	Method:BGPF12
Lower explosive limit	1,4 % (v/v)	Method:Not specified Remark:propellant
Upper explosive limit	11,2 % (v/v)	Method:Not specified Remark:propellant
Flash point	not available	Reason for missing data:substance/mixture is a gas
Auto-ignition temperature	470 °C	Method:non specificato Remark:propellant
Decomposition temperature	not available	Reason for missing data:It only applies to authoritative substances and mixtures, organic peroxides and other substances and mixtures that they can decompose
pH	not available	Reason for missing data:substance/mixture is a gas
Kinematic viscosity	not available	Reason for missing data:substance/mixture is a gas
Solubility	not available	Reason for missing data:substance/mixture is a gas
Partition coefficient: n-octanol/water	2,79	Method:non specificato Remark:propellente
Vapour pressure	da 2,5 a 3,2 Bar	Method:non specificato Remark:propellente Temperature: 20 °C
Density and/or relative density	0,817 g/l	Method:internal Temperature: 20 °C
Relative vapour density	not available	
Particle characteristics		
Method:	It only applies to solids	
Size distribution		
Method:	It only applies to solids	
Dustiness		
Method:	It only applies to solids	
Specific surface area		
Method:	It only applies to solids	
Shape		
Method:	It only applies to solids	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Explosive properties	lower propellant explosion limit: 1.8%	Method: not specified
Oxidising properties	the product is not an oxidizing substance	Method: internal

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

Avoid overheating.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008Metabolism, toxicokinetics, mechanism of action and other information

003_111 - DEO MATIC RICARICA TALCO AIR FLOR

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	Not classified (no significant component)

BUTANE

LC50 (Inhalation gas):	1443 mg/l
------------------------	-----------

isobutane

LC50 (Inhalation gas):	1443 mg/l
------------------------	-----------

propan-2-ol

LD50 (Dermal):	13900 mg/kg bw Rat
LD50 (Oral):	5840 mg/kg Rat
LC50 (Inhalation vapours):	25 mg/l/4h Rat

LINALYL ACETATE

LD50 (Dermal):	> 5000 mg/kg rabbit
LD50 (Oral):	> 9000 mg/kg rat

(S)-p-mentha-1,8-diene

LD50 (Dermal):	> 5000 mg/kg bw Rabbit
LD50 (Oral):	4400 mg/kg Male Rat
LC50 (Inhalation vapours):	1,11 mg/l/4h Mouse

PIPERONAL

003_111 - DEO MATIC RICARICA TALCO AIR FLOR

LD50 (Dermal): > 5000 mg/kg rat
LD50 (Oral): 2350 mg/kg rat

musk ketone

LD50 (Oral): > 5000 mg/kg/bw
LC50 (Inhalation mists/powders): 2,99 mg/m³ air

linalool

LD50 (Dermal): 5610 mg/kg rabbit
LD50 (Oral): 2200 mg/kg mouse
LC50 (Inhalation vapours): > 3,2 mg/l 90 min mouse

2H-CHROMEN-2-ONE

LD50 (Dermal): 293 mg/kg bw rat
LD50 (Oral): 290 mg/kg bw rat
LC50 (Inhalation mists/powders): 293 mg/kg rat

geraniol

LD50 (Dermal): > 5000 mg/kg rabbit
LD50 (Oral): 3600 mg/kg bw rat

ALPHA-ISOMETHYL IONONE

LD50 (Dermal): > 2000 mg/kg rat
LD50 (Oral): 1000 mg/kg mouse

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

Respiratory sensitization

Information not available

Skin sensitization

Information not available

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Adverse effects on sexual function and fertility

Information not available

Adverse effects on development of the offspring

Information not available

Effects on or via lactation

Information not available

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

Target organs

Information not available

Route of exposure

Information not available

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available

Route of exposure

Information not available

ASPIRATION HAZARD

Excluded because the aerosol does not allow the accumulation of a significant amount of product in the mouth

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

geraniol

LC50 - for Fish

22 mg/l/96h Danio rerio

EC50 - for Crustacea

10,5 mg/l/48h Daphnia magna

003_111 - DEO MATIC RICARICA TALCO AIR FLOR

EC50 - for Algae / Aquatic Plants 13,1 mg/l/72h *Desmodesmus subspicatus*
 Chronic NOEC for Fish 10 mg/l *Dania rerio*

BUTANE

LC50 - for Fish 24,11 mg/l/96h
 EC50 - for Crustacea 7,02 mg/l/48h
 EC50 - for Algae / Aquatic Plants 7,71 mg/l/72h

LINALYL ACETATE

LC50 - for Fish 11 mg/l/96h
 EC50 - for Crustacea 15 mg/l/48h
 EC50 - for Algae / Aquatic Plants 62 mg/l/72h
 Chronic NOEC for Fish 10 mg/l
 Chronic NOEC for Crustacea 10 mg/l
 Chronic NOEC for Algae / Aquatic Plants 9,6 mg/l

PIPERONAL

LC50 - for Fish 2,5 mg/l/96h
 EC50 - for Crustacea 52 mg/l/48h
 EC50 - for Algae / Aquatic Plants 31 mg/l/72h
 Chronic NOEC for Fish 1,6 mg/l 96h
 Chronic NOEC for Crustacea 22 mg/l 48h
 Chronic NOEC for Algae / Aquatic Plants 0,38 mg/l

ALPHA-ISOMETHYL IONONE

LC50 - for Fish 5,495 mg/l/96h
 EC50 - for Crustacea 1,45 mg/l/48h
 EC50 - for Algae / Aquatic Plants 6,468 mg/l/72h

(S)-p-mentha-1,8-diene

LC50 - for Fish 0,702 mg/l/96h *Pimephales promelas*
 EC50 - for Crustacea 0,36 mg/l/48h *Daphnia magna*
 EC50 - for Algae / Aquatic Plants 0,904 mg/l/72h freshwater algae
 Chronic NOEC for Crustacea 0,074 mg/l/48 h *Daphnia magna*
 Chronic NOEC for Algae / Aquatic Plants 2,62 mg/l/72 h *Desmodesmus subspicatus*

propan-2-ol

LC50 - for Fish 9640 mg/l/96h
 EC50 - for Crustacea > 100 mg/l/48h

PROPANE

LC50 - for Fish 24,11 mg/l/96h
 EC50 - for Crustacea 7,02 mg/l/96h
 EC50 - for Algae / Aquatic Plants 7,71 mg/l/72h

003_111 - DEO MATIC RICARICA TALCO AIR FLOR

isobutane

LC50 - for Fish 24,11 mg/l/96h

EC50 - for Algae / Aquatic Plants 7,71 mg/l/72h

linalool

LC50 - for Fish 27,8 mg/l/96h *Oncorhynchus mykiss*EC50 - for Crustacea 59 mg/l/48h *Daphnia magna*EC50 - for Algae / Aquatic Plants 88,3 mg/l/72h *Desmodesmus subspicatus*Chronic NOEC for Fish < 3,5 mg/l *Oncorhynchus mykiss*

2H-CHROMEN-2-ONE

LC50 - for Fish 1,324 mg/l/96h

EC50 - for Crustacea 8,012 mg/l/48h

EC50 - for Algae / Aquatic Plants 1,452 mg/l/72h

Chronic NOEC for Fish 0,119 mg/l

Chronic NOEC for Crustacea 0,448 mg/l

Chronic NOEC for Algae / Aquatic Plants 0,408 mg/l

12.2. Persistence and degradability

geraniol

Rapidly degradable

BUTANE

Solubility in water 0,1 - 100 mg/l

Rapidly degradable

LINALYL ACETATE

Rapidly degradable

PIPERONAL

Rapidly degradable

ALPHA-ISOMETHYL IONONE

Entirely degradable

(S)-p-mentha-1,8-diene

Rapidly degradable

propan-2-ol

Rapidly degradable

PROPANE

Solubility in water 0,1 - 100 mg/l

Rapidly degradable

003_111 - DEO MATIC RICARICA TALCO AIR FLOR

linalool

Rapidly degradable

2H-CHROMEN-2-ONE

Rapidly degradable

12.3. Bioaccumulative potential

BUTANE

Partition coefficient: n-octanol/water 1,09

LINALYL ACETATE

BCF 173,9 l/kg

ALPHA-ISOMETHYL IONONE

BCF 726,4 l/kg

(S)-p-mentha-1,8-diene

Partition coefficient: n-octanol/water 4,53

BCF 683 L/kg ww

propan-2-ol

Partition coefficient: n-octanol/water 0,05

PROPANE

Partition coefficient: n-octanol/water 1,09

12.4. Mobility in soil

geraniol

Partition coefficient: soil/water 1,85

LINALYL ACETATE

Partition coefficient: soil/water 2,71

ALPHA-ISOMETHYL IONONE

Partition coefficient: soil/water 3,038 a 20°C

(S)-p-mentha-1,8-diene

Partition coefficient: soil/water 3,383 at 20°C

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number or ID number**

ADR / RID, IMDG, IATA: 1950

14.2. UN proper shipping name

ADR / RID: AEROSOLS

IMDG: AEROSOLS

IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1

IMDG: Class: 2 Label: 2.1

IATA: Class: 2 Label: 2.1

**14.4. Packing group**

ADR / RID, IMDG, IATA: -

14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
IMDG:	Special provision: - EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 150 Kg	Packaging instructions: 203
	Pass.:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Special provision:	A145, A167, A802	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EU: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product
Point 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 2: Hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A	Flammable gas, category 1A
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Press. Gas	Pressurised gas
Press. Gas (Liq.)	Liquefied gas
Carc. 2	Carcinogenicity, category 2
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may burst if heated.
H351	Suspected of causing cancer.

003_111 - DEO MATIC RICARICA TALCO AIR FLOR

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148

003_111 - DEO MATIC RICARICA TALCO AIR FLOR

- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

02 / 03 / 09 / 11 / 12 / 15 / 16.